



FICHA TÉCNICA PADS ABRASIVOS

FLOOR PADS

COLOUR	FIBER	WEIGHT gr/mq.	THICKNESS mm.	RESIN	WEIGHT ABRASIVE %	KIND ABRASIVE	FOR MACHINE UP TO ..
0690 WHITE	VIRGIN POLYESTER	930	23 +/- 10%	Thermoplastic resin	20%	Alluminium Hydrate	1000 t/m
6601 BEIGE/TAN	VIRGIN POLYESTER	1000	23 +/- 10%	Thermoplastic resin	20%	Alluminium Hydrate	600 t/m
6105 RED	VIRGIN POLYESTER	950	24 +/- 10%	Thermoplastic resin	15%	Alluminium Hydrate	600 t/m
6103 BLUE	VIRGIN POLYESTER	1050	23 +/- 10%	Synthetic Thermosetting	12,5%	Alluminium Hydrate	600 t/m
6602 GREEN	VIRGIN POLYESTER	1750	21 +/- 10%	Synthetic Thermosetting	40%	Corundum	300 t/m
6106 BROWN	VIRGIN POLYESTER	1925	21 +/- 10%	Synthetic Thermosetting	46%	Corundum	300 t/m
6604 BLACK	VIRGIN POLYESTER	2250	21 +/- 10%	Synthetic Thermosetting	66%	Corundum	300 t/m
8804 BLACK FORCE	VIRGIN POLYESTER	2400	20 +/- 10%	Synthetic Thermosetting	70%	Corundum	300 t/m
6700 SAPPHIRE	VIRGIN POLYESTER	875	22 +/- 10 %	Thermoplastic resin	8%	Alluminium Hydrate	2000 t/m
6800 RUBY	VIRGIN POLYESTER	1150	22 +/- 10%	Synthetic Thermosetting	15%	Alluminium Hydrate	1500 t/m
0500 NATURAL	VIRGIN POLYESTER AND NATURAL POILS	1000	22 +/- 10%	Thermoplastic resin	0%		600 t/m
0800 NATURAL FORCE	VIRGIN POLYESTER AND NATURAL POILS	2000	22 +/- 10%	Thermoplastic Resin	0%	Alluminium Hydrate	600 t/m

- Para todos os valores acima deverá ser considerada uma tolerância de +/- 5%